


PIN INSULATED TERMINALS

Lead section: 0.5~1.5mm² (22~16) max current=19A

ITEM.NO.	F φ (mm)	Dimension (mm)			Color
		L	H	D φ	
PTV1.25-9	1.9	19.0	10.0	4.3	Red
PTV1.25-10	1.9	20.0			
PTV1.25-12	1.9	22.0			
PTV1.25-13	1.9	23.0			



Lead section: 1.5~2.5mm² (16~14) max current=27A

ITEM.NO.	F φ (mm)	Dimension (mm)			Color
		L	H	D φ	
PTV2-9	1.9	19.0	10.0	4.9	Blue
PTV2-10	1.9	20.0			
PTV2-12	1.9	22.0			
PTV2-13	1.9	23.0			




Lead section: 4~6mm² (12~10) max current=48A

ITEM.NO.	F φ (mm)	Dimension (mm)			Color
		L	H	D φ	
PTV5.5-13	2.8	25.5	12.5	6.7	Yellow

Lead section: 0.5~1.5mm² (22~16) max current=19A

ITEM.NO.	Dimension (mm)			
	W	L	F	C
BDV1.25-10	2.3	20.0	10.0	4.3
BDV1.25-11	3.0	21.0	11.0	
BDV1.25-14	3.0	24.0	14.0	
BDV1.25-18	2.3	28.0	18.0	



Lead section: 1.5~2.5mm² (16~14) max current=19A

ITEM.NO.	Dimension (mm)			
	W	L	F	C
BDV2-9	2.8	19.0	9.0	4.9
BDV2-18	2.3	28.0	18.0	

Lead section: 4~6mm² (12~10) max current=48A

ITEM.NO.	Dimension (mm)			
	W	L	F	C
BDV5.5-10	2.8	22.5	10.0	5.6